CCTV SPECIFICATIONS FOR TENDER

S. NO.	ITEMS WITH SPECIFICATIONS	QUANTITY
NETWORK	VIDEO RECORDERS	
1	 16 Channel NVR H.265+ SUPPORT 300+ MBPS BANDWIDTH SUPPORT 12 MEGAPIXEL SUPPORT 1 HDMI 1 VGA INTELLIGENT FEATURES SUPPORT 4K ULTRA HD SUPPORT 2 SATA HDD PORTS, 8TB CAPACITY EACH 2 USB PORTS SUPPORT 2 X 6TB SURVEILLANCE HARD DRIVE 	03
CAMERAS	Multi Output (Optional)	
2	 8 Megapixel PTZ DOME CAMERA Night Vision H.265 SUPPORT 30X OPTICAL ZOOM 25/30 FPS @ 4K/8 MEGAPIXEL AUTO TRACKING SUPPORT IR LENGTH OF MINIMUM 200 METERS IP67 IK10 SUPPORT PRIVACY MASKING SUPPORT 	01
2	INTELLIGENT FEATURES SUPPORT LOVISTICK FOR DIT SPEED DOME CAMERA	01
3 4	JOY STICK FOR PTZ SPEED DOME CAMERA 4 MEGAPIXEL CAMERA Night Vision H.265+ SUPPORT 25/30FPS @ 4 MEGAPIXEL WIDE DYNAMIC RANGE 2.7mm to12mm (MOTORIZED ZOOM LENS) AUDIO IN AND OUT SUPPORT IR LENGTH OF 50 METERS PRIVACY MASKING SUPPORT INTELLIGENT FEATURES SUPPORT SD MEMORY SUPPORT IP67 POE	01 05
5	 4 MEGAPIXEL CAMERA Night Vision H.265+ SUPPORT 25/30FPS @ 4 MEGAPIXEL WIDE DYNAMIC RANGE FIX LENS DIGITAL ZOOM SUPPORT INTELLIGENT FEATURES SUPPORT 	37

		1
	AUDIO IN AND OUT SUPPORT	
	IR LENGTH OF 50 METERS	
	 PRIVACY MASKING SUPPORT 	
	SD MEMORY SUPPORT	
	• IP67	
	• POE	
CABLING		
6	CAT 6 UTP HIGH QUALITY CABLE	RFT
	BARE STANDARD COPPER CONDUCTOR	(AS PER
	• 23AWG	REQUIREMENT
	PURE COPPER	DURING
	HIGH QUALITY DUCT PATI MUST BE FIXED ON SCREW	INSTALLATION)
7	2 CORE POWER CABLE 3/29 PURE COPPER, HIGH	RFT
	QUALITY	(AS PER
	 HIGH QUALITY DUCT PATI MUST BE FIXED ON SCREW 	REQUIREMENT
		DURING
		INSTALLATION)
DISPLAY S	CREEN	
8	ORIGINAL 55" 4K LED TV (Compatible with NVR Device)	03
	• HDMI	
	• USB	
	TV In/Out	
	- TV III, Out	
POWER B	ACKUP	
9	 3 KVA LINE INTERACTIVE UPS (IMPORTED/BRANDED) 	01
	 4 X 150 AH MAINTENANCE FREE DRY BATTERIES 	
	(IMPORTED/BRANDED)	
NETWORK	SWITCHES	
10	8-PORT POE SWITCH	AS PER
	• 1 X 1000 BASE-X	REQUIREMENT
	• 1 X 10/100/1000 BASE-T	DURING
	• 8 X 10/100 BASE-T	INSTALLATION
	INDUSTRIAL WIDE TEMPERATURE DESIGN	
	MORE THAN 7K CAPACITY OF MAC ADDRESS LIST	
	INDUSTRIAL POE SWITCH (TWO-LAYER)	
	CONFORM IEEE802.3,	
	• IEEE802.3U,	
	IEEE802.3AB/Z AND IEEE802.3X STANDARDS	
	SUPPORT IEEE802.3AF,	
	IEEE802.3AT STANDARD	
11	16-PORT POE SWITCH	AS PER
	• 2 X 10/100/1000 BASE-T (COMBO PORT)	REQUIREMENT
	2 X 1000 BASE-X (COMBO SFP PORT)	DURING
	• 16 X 10/100 BASE-T (POE POWER SUPPLY)	
	200 METERS+ LONG DISTANCE POE TRANSMISSION	INSTALLATION
	POE MANAGEMENT, POE SETTING/EVENT	
	STATISTICS/GREEN POE	
	POE BUDGET: 190W	
	SUPPORT POE, POE+, HI-POE	

	'ORANGE PORT' SUPPORT HI-POE, CAN BE USED WITH THE POE EXTENDER LAYER 2 MANAGEMENT POE SWITCH SUPPORT WEB MANAGEMENT SEARCH AND UPGRADE VIA CONFIGURATION TOOL HIGH LIGHTNING PROTECTION DESIGN NON-BLOCKING VIDEO TRANSMISSION	
12	 HIGH QUALITY 4U CABINET FOR SWITCHES GLASS DOOR 	AS PER REQUIREMENT
	• FAN	
	11.77	DURING
	RCC CANOPY FOR OUT DOOR 4U CABINET (IF REQUIRED)	INSTALLATION
13	HIGH QUALITY (IMPORTED) 27 U CABINET FOR NVR, SWITCH & UPS	01
	27U RACK 600 X 800 PERFORATED RACK A FIX TRAY	
	• 1 FIX TRAY	
	1 SLIDING TRAY	
	• 4 FANS	
	24 PORT PATCH PANEL LOADED	
	CABLE MANAGER	
1	12 WAY UNIVERSAL PDU	

Security In-charge